











STANDARD TYPE SOLENOID OPERATED DIRECTIONAL VALVE



 Plug in connection  (Spool type : 3C2)	MOUNTING STANDARD : (CETOP 03, CETOP 05), (NG 6, NG 10), ISO 4401							
	CONNECTION TYPE PLUG IN TYPE				MAXIMUM W. P. : 315 KG/CM ²			
	CODE	SIZE	VALVE POSITION	SPOOL - SPRING POSITION	SPOOL TYPE	COIL		FLOW l/min
DSG-03-3C2-A240-N1-50	3/8"	THREE POSITION	SPRING CENTERED	2	Ac 240	ROUND	120	3914.00


 	1/8" & 3/8" RELIEF MODULAR VALVE FOR P. LINE					
	CODE	SIZE	PRESSURE ADJU RANGE (KG F/CM ²)	MAXI OPERATING L/MIN PRESSURE	FLOW	PRICE
	MBP-01-C-30	1/8"	C : 08-140	140	35	1648.00
MBP-03-H-20	3/8"	H : 35-250	250	70	2121.00	

 	1/8" & 3/8" REDUCING MODULAR VALVE FOR P. LINE					
	CODE	SIZE	B : 8 - 70	70	35	-----
	MRP-01B-30	1/8"	B : 8 - 70	70	35	-----
MRP-03H-20	3/8"	H : 35-210	210	50	2121.00	




 	3/8" REDUCING MODULAR VALVE FOR P. LINE					
	CODE	SIZE	X METER OUT	-----	35	-----
	MSW-01-X-30	1/8"	X METER OUT	-----	35	-----
MSW-03-Y-20	3/8"	Y METER IN	-----	70	1915.00	

 	CODE	SIZE	CRACKING Kgf. / cm ²	MOUNTING	FLOW l/min	PRICE
	YBT-01-B-1080	1/4"	B : 8-70	THREADED	20	617.00
	YBT-03-B	3/8"	B : 8-70	THREADED	20	556.00
	YBT-01-C-1080	1/4"	C : 35-140	THREADED	20	617.00
	YBT-03-C	3/8"	C : 35-140	THREADED	20	556.00

 	YBG-01-B-1080	1/4"	B : 8-70	SUB-PLATE	20	617.00
	YBG-03-B	3/8"	B : 8-70	SUB-PLATE	20	556.00
	YBG-01-C-1080	1/4"	C : 35-140	SUB-PLATE	20	617.00
	YBG-03-C	3/8"	C : 35-140	SUB-PLATE	20	556.00






REMOTE CONTROL RELIEF VALVE  W. P. : 250 kg/cm ²	CODE	SIZE	CRACKING Kgf. / cm ²	MOUNTING	FLOW l/min	PRICE
	YBT-01-1080	1/4"		THREADED	4	617.00
	YBG-01-1080	1/4"		SUB-PLATE	4	617.00

COIL FOR SOLENOID VALVE








ROUND SHAPE PLUG IN TYPE COIL WITH LIGHT INDICATOR CONNECTOR 	CODE	SIZE	PRICE	 	CODE	SIZE	PULL TYPE	MOUNTING	FLOW	PRICE
	RC 02 A110 (AC 110 V)	1/4"	921.00		PILOT OPERATED RELIEF VALVE W. P. : 250 kg/cm ²					
	RC 02 D24 (DC 24 V)	1/4"	921.00		BG - 03 - P	3/8"	-----	SUB - PLATE	100	2626.00
	RC 03 D24 (DC 24)	3/8"	1611.00		BG - 06 - P	3/4"		SUB - PLATE	200	3192.00

CHECK VALVE CARBON STEEL HYDRAULIC Q. R. C.

MOUNTING STANDARD : (CETOP 03, CETOP 05), (NG 6, NG 10), ISO 4401 (AS PER ISO - 7241 A)

CHECK MODULAR VALVE FOR P. LINE W. P. 250 kg/cm ²						SOCKET MALE (SM)	CODE	SIZE INCH	W. P Kg/Cm ²	PRICE
  P=P Port Only 	CODE	SIZE	CRACKING PRESS. RANGE (kg f/cm ²)	FLOW L/min	PRICE		 HSM - 04 1/2"	350	-----	
	MCP-01-2-31	1/8"	2	35	1504.00	 HPM - 04 1/2" HPM - 05 3/4"				350
MCP-03-2-10	3/8"	2	70	2121.00						

BRASS HYDRAULIC Q. R. C. (AS PER ISO - 7241 B)

  T=T Port Only 	MCT-01-2-31	1/8"	2	35	1504.00	 KSM - 04 1/2" KSM - 05 3/4"	45	617.00 977.00
	MCT-03-2-10	3/8"	2	70	2121.00			
 W=A & B Port Only 	MPW-03-2-10	3/8"	2	70	2121.00	 KPM - 04 1/2" KPM - 05 3/4"	45	266.00 419.00

RIGHT ANGLE CHECK VALVE FLAT FACE TYPE Q. R. C. (AS PER ISO16028)

W. P. 250 kg/cm²

CODE	SIZE	PULL TYPE	MOUNTING	FLOW	PRICE	PLUG FEMALE (PF)	QKPF - 02 1/4"	W. P 350 Kg/Cm ²	284.00
CRG-03-50	3/8"	3.5	SUB - PLATE	40	706.00				
CRG-06-50-30	3/4"	3.5	SUB - PLATE	125	574.00		378.00		

SmsN SINGLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R1 AT / DIN 20022 - 1SN / EN 853- 1SN

CODE	ID (Inch)	ID (mm)			O. D. (mm)	W. P. (Bar)	B. P. (Bar)	Mini Bending radius (mm)	Coil Length	PRICE MTR
		Std. Size	Min	Max						
SR1 - 06	1/4"	6.30	6.20	7.00	14.10	225	900	100	85-110	144.00
SR1 - 16	5/8"	16.00	15.50	16.70	24.50	130	520	200	85-110	253.00
SR1 - 25	1"	25.00	25.00	26.40	36.60	88	350	300	50-60	421.00

SmsN DOUBLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R2 AT / DIN 20022 - 2SN / EN 853-2SN

SR2 - 32	1-1/4"	31.50	31.40	33.00	49.50	125	500	420	20	941.85
----------	--------	-------	-------	-------	-------	-----	-----	-----	----	--------

SmsN FOUR STEEL WIRE BRAIDED SPIRAL HOSE

EXCEED SAE 100 R12 / R13 & CONFORMS TO DIN 20023/EN856 - 4SP - 4SH

4SP - 12	1/2"	12.5	12.30	13.50	25.4	415	1660	230	20	688.00
----------	------	------	-------	-------	------	-----	------	-----	----	--------