













## CHECK VALVE CARBON STEEL HYDRAULIC Q. R. C.

MOUNTING STANDARD : (CETOP 03, CETOP 05), (NG 6, NG 10), ISO 4401 (AS PER ISO - 7241 A)


CHECK MODULAR VALVE FOR P. LINE W. P. 250 kg/cm <sup>2</sup>						SOCKET MALE (SM)	CODE	SIZE INCH	W. P Kg/Cm <sup>2</sup>	PRICE
  P=P Port Only 	CODE	SIZE	CRACKING PRESS. RANGE (kg f/cm <sup>2</sup> )	FLOW L/min	PRICE		 HSM - 04 1/2"	1/2"	350	-----
	MCP-01-2-31	1/8"	2	35	1504.00	 PLUG MALE (PM)		HPM - 04	1/2"	350
MCP-03-2-10	3/8"	2	70	2121.00	HPM - 05		3/4"	350	221.00	

## BRASS HYDRAULIC Q. R. C. (AS PER ISO - 7241 B)

  T=T Port Only 	MCT-01-2-31	1/8"	2	35	1504.00	 SOCKET FEMALE (SM)	KSM - 04	1/2"	45	617.00
	MCT-03-2-10	3/8"	2	70	2121.00		KSM - 05	3/4"	45	977.00
  W=A & B Port Only	MPW-03-2-10	3/8"	2	70	2121.00	 PLUG FEMALE (PM)	KPM - 04	1/2"	45	266.00
								KPM - 05	3/4"	45

## RIGHT ANGLE CHECK VALVE FLAT FACE TYPE Q. R. C. (AS PER ISO16028)

W. P. 250 kg/cm<sup>2</sup>

CODE	SIZE	PULL TYPE	MOUNTING	FLOW	PRICE	 PLUG FEMALE (PF)	QKPF - 02	1/4"	W. P 350 Kg/Cm <sup>2</sup>	284.00
CRG-03-50	3/8"	3.5	SUB - PLATE	40	706.00		QKPF - 03	3/8"		364.00
CRG-06-50-30	3/4"	3.5	SUB - PLATE	125	574.00		QKPF - 04	1/2"		378.00

## SmsN SINGLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R1 AT / DIN 20022 - 1SN / EN 853- 1SN

CODE	ID (Inch)	ID (mm)			O. D. (mm)	W. P. (Bar)	B. P. (Bar)	Mini Bending radius (mm)	Coil Length	PRICE MTR
		Std. Size	Min	Max						
SR1 - 06	1/4"	6.30	6.20	7.00	14.10	225	900	100	85-110	144.00
SR1 - 16	5/8"	16.00	15.50	16.70	24.50	130	520	200	85-110	253.00
SR1 - 25	1"	25.00	25.00	26.40	36.60	88	350	300	50-60	421.00

## SmsN DOUBLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R2 AT / DIN 20022 - 2SN / EN 853-2SN

SR2 - 32	1-1/4"	31.50	31.40	33.00	49.50	125	500	420	20	941.85
----------	--------	-------	-------	-------	-------	-----	-----	-----	----	--------

## SmsN FOUR STEEL WIRE BRAIDED SPIRAL HOSE

EXCEED SAE 100 R12 / R13 & CONFORMS TO DIN 20023/EN856 - 4SP - 4SH

4SP - 12	1/2"	12.5	12.30	13.50	25.4	415	1660	230	20	688.00
----------	------	------	-------	-------	------	-----	------	-----	----	--------