



SmsN SINGLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R1 AT / DIN 20022 - 1SN / EN 853- 1SN


CODE	ID (Inch)	ID (mm)			O. D. (mm)	W. P. (Bar)	B. P. (Bar)	Mini Bending radius (mm)	Coil Length	PRICE MTR
		Std. Size	Min	Max						
SR1 - 06	1/4"	6.30	6.20	7.00	14.10	225	900	100	85-110	144.00
SR1 - 13	1/2"	12.50	12.30	13.50	21.40	160	640	180	85-110	-----
SR1 - 16	5/8"	16.00	15.50	16.70	24.50	130	520	200	85-110	253.00
SR1 - 25	1"	25.00	25.00	26.40	36.60	88	350	300	50-60	421.00



SmsN DOUBLE STEEL WIRE BRAIDED HYDRAULIC HOSE

CONFORMS SAE 100 R2 AT / DIN 20022 - 2SN / EN 853-2SN


SR2 - 32	1-1/4"	31.50	31.40	33.00	49.50	125	500	420	20	941.85
----------	--------	-------	-------	-------	-------	-----	-----	-----	----	--------



SmsN FOUR STEEL WIRE BRAIDED SPIRAL HOSE

EXCEED SAE 100 R12 / R13 & CONFORMS TO DIN 20023/EN856 - 4SP - 4SH

4SP - 12	1/2"	12.5	12.30	13.50	25.4	415	1660	230	20	688.00
4SH - 19	3/4"	19.0	18.60	19.80	31.4	420	1680	280	20	-----







THUNDER SPRING HOSE (NON TOXIC, FOOD GRADE)

STRUCTURE : SOFT P.V.C. HOSE WITH EMBEDDED STEEL WIRE REINFORCED. TEMP. RANGE : -10°C to +60°C
 COLOR : CRYSTAL CLEAR TRANSPARENT HOSE FEATURE : IN SIDE & OUT SIDE SMOOTH SURFACE VERY FLEXIBLE & LIGHT IN WEIGHT

CODE	ID MM	OD MM	ID INCH	PRESS. KG/CM ² at 27°C		VACUUM MH ₂ O	VACUUM mmHg	COIL LENGTH MTR	PRICE PER MTR
				W.P.	B.P.				
STWH064	64	76	2-1/2"	5	15	8.0	600	20	910.00
STWH100	102	116	4"	5	15	7.0	500	20	1809.00

SPARE PARTS FOR SOLENOID VALVE

DESCRIPTION	CODE	SIZE	PRICE	DESCRIPTION	CODE	SIZE	PRICE
 FOR  COMPLETE PISTON WITH TEFLON WASHER & SPRING SUITABLE FOR 2/2 DIRECT ACTING SERVO OPERATED VALVE	L2012D17	1/2"	700.00	 FOR  COIL W/O COVER AC110V & AC220V & DC24V AVAILABLE 2/2 DIRECT ACTING SERVO OPERATED VALVE	L2012D17	1/2"	910.00
	L2020D17	3/4"	700.00		L2020D17	3/4"	910.00
	L2525D22	1"	700.00		L2525D22	1"	910.00
	L2038D35	1-1/2"	1400.00		L2038D35	1-1/2"	1190.00
	L2050D50	2"	1680.00		L2050D50	2"	1190.00
 FOR  COIL W/O COVER AC110V & AC220V & DC24V AVAILABLE 2/2 DIRECT ACTING DIAPHRAM TYPE SOLENOID VALVE	W2006D02	1/4"	280.00	 FOR  RUBBER DIAPHRAM SUITABLE FOR 2/2 DIRECT ACTING DIAPHRAM TYPE SOLENOID VALVE	W2012D16	1/2"	280.00
	W2010D04	3/8"	420.00		W2020D20	3/4"	280.00
	W2012D16	1/2"	420.00		W2025D25	1"	-----
	W2020D20	3/4"	420.00		W2031D35	1-1/4"	420.00
	W2025D25	1"	420.00		W2038D40	1-1/2"	420.00
	W2031D35	1-1/4"	840.00		W2050D50	2"	560.00
	W2038D40	1-1/2"	840.00				
	W2050D50	2"	840.00				